



EDRILL VENCEDOR

A purpose built semi-submersible self-erecting tender assisted drilling rig featuring 10k dual BOP, off-line pipe handling, stand building and designed to work on TLPs and SPARs in up to 6,500 ft of water with pre-laid mooring.

GENERAL	
Design	KFELS SS3600E-GOM-C42
Built / Year	Keppel FELS Singapore / 2009
Rig Type	SSETR
Major Upgrades	Nil
Flag	Panama
Classification	ABS
Class Notations	+A1 Column Stabilized Drilling Tender
MAIN DIMENSIONS / TECHNICAL	
Length x Breadth	308 ft x 118 ft x 67 ft
Max. Water Depth	6,500 ft
Min. Water Depth	32 ft
Drilling Depth	30,000 ft
Variable Load	3,600 mt
Helideck	S61N / S92
Helideck Compliance	CAP437
Accommodation	160
DRILLING EQUIPMENT	
Derrick	MH-Pyramid, quadruple
Hookload	1,000 kips
Drawworks	LEWCO LDW 3000 - 3,000 HP
Racking Capacity	21,600 ft 5" DP
Top Drive	NOV TDS-8S AC, 750 st, 63,000 ft-lbs cont torque
Pipe Handling	PH-100
Iron Roughneck	Forum, Model FH-80
Rotary Table	LEWCO L495 - 49.5"
Power Slips	PS-21
Drilling Line	5,000 ft x 1 1/2" OD
Crown Block	500 t
DES Number of Lifts	15
Max. Platform Height	110 ft
STORAGE CAPACITIES	
Fuel	10,435 bbls
Drill Water	14,379 bbls
Potable Water	6,542 bbls
Liquid Mud	5,491 bbls
Base Oil	3,384 bbls
Brine	3,371 bbls
Barite / Bentonite	5,200 / 1,766 cu ft
Cement	6,400 cu ft
Sack Storage	9,000 Sacks

POWER	
Main Engines	6 x Cat 3516-BTA
Main Generators	6 x KATO AC 6P7-2050 @ 1,600 kW
Total Power	7,800 kW
Emergency Power	1 x Cat 3512BTA, KATO 6p6 @ 1020 kW
WELL CONTROL	
Diverter	21 -1/4" Diverter Spool, 2K
BOP	13-5/8" Cameron, 10k ABOP 13.5/8" Cameron, 10k 2x SRBOP & 2x DRBOP
C&K Manifold	10k psi
BOP Hoist	37.5 mt
MUD SYSTEM	
Mud Pumps	4 x LEWCO w-1712, triplex, 1,600 HP
Pressure Rating	7,500 psi
Shale Shakers	4 x Brandt VSM 300
Mud Gas Separator	30" OD with 8" OD vent line
Degasser	SWACO CD-1400 Hurricane
LIFTING EQUIPMENT	
Main Crane	Favco PC300 / 170-ft Boom
Main Crane Rating	250 mt @ 22.5 m Radius (DF = 2.0)
Deck Crane	Favelle Favco 7.5/10K with 140-ft Boom
Deck Crane Rating	44 mt @ 7.5 m Radius (DF = 2.0)
Master Skid Cranes	2 x Master Skid Knuckle Joint Cranes
Crane Rating	7,500 lbs
TUBULARS	
Drill Pipe	5" DP
OFFLINE ACTIVITY CAPABILITY	
OAC Crane	Cantilever Crane, 22,000 lbs
OAC Power Tong	Forum, Model FH-80
Offline Electric Log	Yes
STATION KEEPING	
Anchor Wire	8 x 3 OD x 5,000 ft Galvanised Wire Ropes
Anchors	8 x 12 mt Stevpris + 1EA Spare
Mooring Winches	4 x Skagit Smatco Anchor Traction Winches, Model TMW- 300 Dual Drum, Electric
OTHER FEATURES	
	4 x 80 men Norsafe Survival Crafts

Further information: +65 62228366 — <https://edrill.com/contact-us/>

The above information is intended for general reference only. All equipment and specifications are subject to change at any time.